

# iPP 350

---

## The consumer-facing solution for fast & secure payment acceptance

---

- A fast, secure point of sale (POS) and point of payment solution.
- Improve customer experience through an intuitive interface and acceptance of contactless payments.
- Expand consumer choice by accepting multiple methods of electronic payment.
- Speed payment system integration with seamless plug-and-play installation.



security



smartcard



magstripe



contactless



color display

## Countertop checkout with a fast, secure payment solution.

### Highest Security

As a PCI PTS 4.x certified solution, the iPP 350 ensures secure data and application management and enables highly secured electronic transactions. The smart terminal also complies with SRED and Open protocol modules. The optional PIN privacy shield ensures PIN-entry confidentiality.

### All Payment Options

In addition to accepting EMV chip & PIN, magstripe, and NFC/contactless payments, the iPP 350 also supports new NFC technologies, such as loyalty, and wallets.

### Designed for Retail

Robust and optimized for fast checkout, the iPP 350 is designed to meet the needs of intense retail environments. It is compact, requires minimum counter space and provides easy handling. A large 15-key backlit keypad, LCD display and function keys allow comfortable, convenient interactions.

### All Connectivity & Communication

The iPP 350 connects to an ECR, a POS or a PC via direct connection, such as Ethernet or RS232. This plug-and-play device is equipped with a single multi-point mono connector cable for seamless integration.

### Brand Promotion

The iPP350 enhances brand promotion with a color graphics display, software customization and hardware personalization options (top casing or lens).

### Telium 2 Operating System

Powered by Ingenico, Telium 2 technology is the result of 30 years' of experience in the payment industry. Secure, highly integrated and fast, Telium 2 is a world leading platform for secure payment services. With advanced functions, it can easily manage more than 2,000 graphical libraries and handle new business service apps. Telium 2 is the fully scalable, reliable operating system embedded into Ingenico's 27 million terminals deployed worldwide.



| iPP300 Series           |                          | iPP 350                                      |
|-------------------------|--------------------------|--|
| Processor               | ARM 9 & ARM 7            | ●  |
| Memory                  | 128 MB flash             | ●  |
|                         | 32 MB SDRAM              | ●  |
|                         | μSD supporting up to 8G  | ●  |
| SAM                     |                          | 3  |
| Card Readers            | Smart card               | ●  |
|                         | Magstripe                | ●  |
|                         | Contactless              | ●  |
| Display                 |                          | LCD 128 x 64<br>Color                        |
| Terminal Connectivity   |                          | USB<br>RS232<br>Ethernet                     |
| Keypad                  | Backlit operational keys | 15   |
| Audio                   | Buzzer                   | ●  |
| Power Supply            | Powered USB              | 5V 500 mA                                    |
|                         | Powered RS232            | 5V or 12V                                    |
|                         | Powered Ethernet         | POE compliant with 802.3af                   |
|                         | External power supply    | Optional                                     |
| Terminal Size           | L x W x H                | 6.61" x 3.26" x 1.57"                        |
| Weight                  |                          | 9.41 oz                                      |
| Relative Humidity       |                          | 85% HR to 131°F (55°C)                       |
| Optional Privacy Shield | PCI compliant            | Additional or factory-mounted privacy shield |
| Environment             | Operating temperature    | 32°F to 113°F (0°C to +45°C)                 |
|                         | Storage temperature      | -4 to 131°F (+20°C to +55°C)                 |
| Security                | Online & offline         | PCI PTS 4.x certified                        |

USA\_Datasheet\_iPP350\_IQWL\_201012. All rights reserved. This document is not binding and the specifications above can be modified without prior consent. ©2020



www.ingenico.us

**ingenico**  
aWorldlinebrand